

GUARD-FLEX - FLEXIBLE GUARDRAIL DELINEATOR BRACKET
GF1 - GF2 - GF3

DIMENSIONS AND SPECIFICATIONS

Overall Width (facing traffic)	90mm
Delineator face width	85mm
Depth	12mm
Height - GF1	85mm Diameter - Circular
Height - GF2	75mm x 40mm - Rectangular
Height - GF3	145mm Top - Triangular
Angle	90°

DEFINITION

The Guard-Flex Flexible Guardrail delineator brackets are manufactured from specially formulated polyurethane Compound and have been weather tested for 10 years. No change in physical properties when subjected to temperatures as low as 30° Celsius to as high as +60° Celsius.

DURABILITY

Guard-Flex Guardrail delineator brackets are designed to easily fit into existing guardrail bolting systems. The Guard-Flex Guardrail delineator brackets can be glued onto concrete barriers using an optional galvanised steel adaptor plate to which Hilti CA268 Fast Setting Adhesive Paste or equivalent is applied.

FINISH & COLOUR

All faces of the Guard-Flex delineator brackets are smooth, free of any sharp edges and can be delineated in Red, White or Yellow to both sides or to the front only.

DELINEATORS

The Guard-Flex Flexible Guardrail delineator brackets are fitted with CL1 reflective material which complies with AS1906.1 and all other relevant standards.

GUARD-FLEX - FLEXIBLE GUARDRAIL DELINEATOR BRACKET

Product code: GF1 / GF2 / GF3

DIMENSIONS AND SPECIFICATIONS

Overall Width (facing traffic)	90mm
Delineator face width	85mm
Depth	12mm
Height-GF1	85mm Diameter - Circular
Height-GF2	75mm x 40 mm - Rectangular
Height-GF3	145mm Top - Triangular
Angle	90°

DEFINITION

The Guard-Flex Flexible Guardrail delineator brackets are manufactured from specially formulated polyurethane Compound and have been weather tested for 10 years. No change in physical properties when subjected to temperatures as low as 30° Celsius to as high as +60° Celsius.

DURABILITY

Guard-Flex Guardrail delineator brackets are designed to easily fit into existing guardrail bolting systems. The Guard-Flex Guardrail delineator brackets can be glued onto concrete barriers using an optional galvanised steel adaptor plate to which Hilti CA268 Fast Setting Adhesive Paste or equivalent is applied.

DELINEATORS

The Guard-Flex Flexible Guardrail delineator brackets are fitted with CL1 reflective material which complies with AS1906.1 and all other relevant standards.

FINISH & COLOUR

All faces of the Guard-Flex delineator brackets are smooth, free of any sharp edges and can be delineated in Red, White or Yellow to both sides or to the front only.